

UL-50 WOD SERIES WOD-30DDC-UL50



Why Choose the WOD-UL Series?

The WOD-30DDC-UL50 enclosure is the pinnacle of enclosures. With a fully welded chassis, heavy duty vulcanized gasketing and years of design and engineering behind it, you will find this will meet the most stringent requirements of the UL-50E Type 4 listing. Fully tested by a third party Nationally Recognized Testing Laboratory and listed to the UL-50E standard, you can trust that the WOD UL series will pass any test or inspection it faces. Designed with public safety requirements in mind, these units can be place in mission critical locations where communication or sensitive gear needs to be protected regardless of the situation. As with the standard WOD series, the WOD-UL series comes with standard 3-point locking, front and rear access with integrated wind locks, top mounted solar shield, adjustable R-strut racking, reversible 19" or 23" EIA racking, Alumiflex construction and our unmatched 15-year warranty. Moreover, there is an extensive list of optional accessories including HVAC units, electrical panels, and cable entry solutions to name a few. No matter the application, DDB provides cutting-edge design, competitive pricing, benchmark lead times, and guaranteed delivery. Whether you require a custom enclosure or something from our substantial stock, our professional staff is here to help you today.

Application Types

Telecommunications Wireless/Broadband Fiber Optics Back Haul Public Safety DAS Utility Base Station Military Trailer-Based Communications Wi-Fi LTEE/4G/5G

2301 S. HWY 77 Pauls Valley, OK 73075 T: (405)-665-2876 sales@ddbunlimited.com



Environmental & Safety Ratings:

- ✓ ETL environmentally listed to UL 50/50E, IP 66, Type 4
- ✓ ETL listed; Safety Requirements, UL 62368-1:2019 Ed.3, CSA C22.2



Features

15 Year Warranty 0.125" Aluminum Construction 3-Point Locking System Heavy Duty Out-Door Construction Front and Rear Access Stainless Steel External Hardware/Hinge Cream Powder-Coat, Standard Wind Locks Quick Shipping


Weight and Dimensions

Approximate Exterior Enclosure Dimensions: 32"H x 33"W x 39"D Shipping Dimensions: 48"L x 42"W x 40"H- Palletized Approximate Shipping Weight: 175 lbs.




UL-50 WOD SERIES WOD-30DDC-UL50







- 1. Alumishield
- 2. Wind Locks
- 3. 19" and 23" Adjustable Racking Rails
- 4. Stainless Steel Door Hinge
- 5. 3-Point Locking System
- 6. Heavy Duty 0.160" Doors
- 7. Powder-Coat Cream
- 8. Rear Door Access

2301 S. HWY 77 Pauls Valley, OK 73075 T: (405)-665-2876 sales@ddbunlimited.com www.ddbunlimited.com Scan this code for Climate Control









File Location: (DD8) (EPDM Vault:) C:\DD8\DR Requests\Customers\DD8 WE8 DWG\WOD Family UL50 WE8\WOD-30DD-UL50 WE8\

